

Nimbus Wet Area RFID Lock with Scheduled Unlock 3966



Product Description

Does your locker room suffer with locker blocking? Avoid the problem and start every day with up to 100% locker availability using the water resistant Nimbus Wet Area RFID with Scheduled Unlock. The feature rich functionality supports up to 50 private mode users at one time and provides a full electronic audit trail for visibility and control.

**Enhanced RFID Features**

- Multiuser private mode with up to 50 concurrent users - PIN code or RFID card
- Up to 3 Master Users
- Log/Audit file creation - Record the date and time for each multiuser private mode lock event against that user
- Audit file accessible by writing to the RFID card - Audit file read by PC card reader and Nimbus RFID software
- Ability to Clone Lock Settings by programming an RFID card, the unprogrammed lock can read the RFID card to replicate the master settings

**Real Time Clock Features**

- Functions to set time and date
- Unlock function allowing unlocking at a fixed time every day to avoid user locker blocking
- Set public mode scheduler which provides the ability to set operating times for everyday of the week - also sets RFID scan times
- Auto unlock after 0-999 minutes after the last lock event
- Note: both auto scheduled unlock function and public mode operating times cannot be set at the same time.

**Standard Features**

- Compatible with ISO14443A RFID standards including Legic-Advant-Protocol and Mifare-Protocols
- **Environmental Protection:** IP65 Rated suitable for use in wet areas / applications
- **Temperature Rating:** -8°C to +50 °C
- **User modes:** Public mode, Private mode, Multiuser mode (Private mode only) or RAS mode
- **Standard finishes:** Black, silver, white powder coat
- **Optional finishes:** Satin or Chrome (MOQ applies)
- **Fitting options:** Surface mount or semi-flush fit fitting (maximum 20mm protrusion)
- **Mounting options:** Vertical and Horizontal (left or right hand fixing, numbers rotated to orientation)
- **Steel Mechanical Override Key:** 2 keys per 50 locks
- **Robust design:** Zinc diecast construction housing
- **Spindle length:** 17mm and 21mm spindle length

- **Lock movement:** Left 90° or Right 90°
- **Cam fixing:** 8mm SQ. with M4 thread
- **Declaration of Conformity:** CE Marked

## Options

Product Code	Body Width	Body Height	Body Depth	IP65
3966	41	140	24.75	Yes